

## CROSS CONNECTORS FOR RK, IK, DLI & SK RANGE

Q, QI

2833.0

Q 3 - 3 pole cross connector for DLI/DLIS 2.5

- Screw in
- Insulated versions
- Can be cut down



### PRODUCT DESCRIPTION

The Q/QI screwable cross-connector system allows you to quickly link terminal blocks of the same size.

The QI range is touch-safe and are generally available in 2, 3, 4 or 10 poles, some variants have up to 98 poles, which can be cut down as required.

With both ranges it is possible to 'skip' over terminals by breaking out the conductor (QI) or removing the screw and sleeve (Q).

## TECHNICAL DATA

### GENERAL DATA

Rated wire cross section	2.5 mm <sup>2</sup>
Max voltage with partition	400 V
Max voltage without partition	400 V
Rated current IEC	20 A
Mounting	Screw in
Contamination degree	3
Additional information	for DLI 2,5/   DLIS 2,5/

### DIMENSIONS

Length	4 mm
Width	16.6 mm
Distance to hole centres	6.1 mm

Pitch	6 mm
Hole diameter	2.8 mm

CONNECTION DATA

Number of poles	3
Screw size	M 2,5
Screw type	Slotted
Torque min	0.4
Torque max	0.8

MATERIALS

Material	Copper
----------	--------

ADDITIONAL DATA

Tariff code	85369010
Country of origin	DE
Weight	2.54 g
Pack size	50