

## CROSS CONNECTORS FOR ZRK/ZST TENSION SPRING RANGE

ZQI

3712.8

ZQI 2.5/4 YE, 4 Way Cross Connector for 2.5mm  
ZSRK/ZRK/ZSL/ZST/ZIZA - Yellow

- For ZRK, ZSRK, ZST and ZINI/ZAKTO
- Insulated plug in
- Can be cut down



### PRODUCT DESCRIPTION

### TECHNICAL DATA

#### GENERAL DATA

|                               |                     |
|-------------------------------|---------------------|
| Rated wire cross section      | 2.5 mm <sup>2</sup> |
| Colour                        | Yellow              |
| Max voltage with partition    | 800 V               |
| Max voltage without partition | 800 V               |
| Rated current IEC             | 24 A                |
| Mounting                      | Push in             |
| Contamination degree          | 3                   |

#### DIMENSIONS

|        |         |
|--------|---------|
| Length | 4.5 mm  |
| Width  | 19.3 mm |
| Pitch  | 5 mm    |

#### CONNECTION DATA

|                 |   |
|-----------------|---|
| Number of poles | 4 |
|-----------------|---|

#### MATERIALS

|                            |               |
|----------------------------|---------------|
| Material                   | Copper alloy  |
| Insulation material        | Polyamide 6.6 |
| Flammability class         | UL94-V2       |
| Operating temperature from | -40 °C        |
| Operating temperature to   | 105 °C        |

**ADDITIONAL DATA**

|                   |          |
|-------------------|----------|
| Tariff code       | 85369010 |
| Country of origin | DE       |
| Weight            | 2.26 g   |
| Pack size         | 20       |