0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

# **CONTACLIP**

## **CROSS CONNECTORS FOR ZRK/ZST TENSION SPRING RANGE**

ZQI

3722.8 ZQI 4/4 YE, 4 Way Cross Connector for 4mm ZSRK/ZRK/ZSL

- For ZRK, ZSRK, ZST and ZINI/ZAKTO
- Insulated plug in
- Can be cut down



#### PRODUCT DESCRIPTION

## **TECHNICAL DATA**

## **GENERAL DATA**

Rated wire cross section	4 mm²
Colour	Yellow
Max voltage with partition	800 V
Max voltage without partition	800 V
Rated current IEC	32 A
Mounting	Push in
Contamination degree	3

### **DIMENSIONS**

Length	4.5 mm
Width	22.3 mm
Pitch	6 mm

## **CONNECTION DATA**

Number of poles	4	
-----------------	---	--

#### **MATERIALS**

Material	Copper alloy
Insulation material	Polyamide 6.6
Flammability class	UL94-V2
Operating temperature from	-40 °C
Operating temperature to	105 °C

## **ADDITIONAL DATA**

Tariff code	85369010
Country of origin	DE
Weight	2.79 g
Pack size	20