**OEM AUTOMATIC**

**OEM Automatic Ltd**
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

**CONTACLIP**

# PICK-OFF TERMINALS AND TEST ADAPTERS

## MAG, SMAG, STA, TA, ZTA, EP

3772.2
ZTA 6, Test adaptor for ZRK/ZSL 6

- STA, SMAG compatible with SRK series
- SMAG extends standard feed-through terminal up to 4 connections
- STA test adapters for SRK series
- TA test adapters dfor RK series
- ZTA Test adaptors for ZIZA/ZRK series

## PRODUCT DESCRIPTION

CONTA-CLIP offers specific and innovative accessories for the SRK I SSL screw connection system.

**Pick-off terminals SMAG**

- The SMAG pick-off terminals make possible one or two additional extra wire connectors onto the SRK terminal blocks and therefore extend the standard feed-through terminal by up to four connectors.
- The SMAGs are mechanically snapped into the SRK terminal blocks.
- The SMAG busbar is connected via the corresponding base connection of the terminal block, the rated cross section is thereby reduced to the next lower size.

**Test adapter STA**

- The ST test adapter can be used to quickly and safely test pre-wired terminal blocks.
- A test plug block can be mounted with any number of poles using the locking pegs and the STA ZP intermediate plate with widths from 1 to 3 mm. The STA ZP intermediate plate allows the assembly of a test plug block, which can also be mounted on different block widths (SRK/SSL 2.5 | 4 | 6 | 10).
- Thanks to its innovative design the STA test adapter can be rotated through 180°. It can therefore also be mounted onto the SRK terminal block, whereby one of the cross-connection channels is already occupied by a cross-connector.

# TECHNICAL DATA

## GENERAL DATA

| Colour | Beige |
|---|---|
| Additional information | for tension-spring terminals 6 mm² |

## DIMENSIONS

| Length | 32.3 mm |
|---|---|
| Pitch | 8.1 mm |

## CONNECTION DATA

| Cross section stranded wire from | 0.5 mm² |
|---|---|
| Cross section stranded wire to | 1 mm² |
| Stripping length | 5 mm |

## MATERIALS

| Insulation material | Polyamide 6.6 |
|---|---|
| Flammability class | UL94-V2 |
| Operating temperature from | -40 °C |
| Operating temperature to | 105 °C |

## ADDITIONAL DATA

| Tariff code | 85369010 |
|---|---|
| Country of origin | DE |
| Weight | 3.08 g |
| Pack size | 10 |