OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

BUSBAR CLAMPING YOKE TERMINALS - ZB SERIES

ZB, SSCH

2138.0
ZB 4, 4mm² clamping yoke for 10 x 3 busbar - no cap



- Screw couplings
- Clamp sizes, 4mm², 16mm² or 35mm²
- Available for 10x3mm or 6x6mm bar
- Material polyamide 6.6 - UL94-V2

PRODUCT DESCRIPTION

Busbars and clamping yokes

The ZB clamping yoke can be used in conjunction with the 10 x 3 or 6 x 6 busbars in order to bring the neutral conductor or Earth (PE) conductor together at one point.

The SH and ES busbar supports are used to mount the busbar, either directly to the back plate or on the DIN rail.
With longer rails, these can be positioned between the clamping yokes to give extra support.

The clamping yokes are available with or without insulating caps, green/yellow as a PE connection, blue for Neutral and Black.

These caps stogether with the labelling tags help the connections wires to be clearly assigned.

TECHNICAL DATA

GENERAL DATA

Rated wire cross section	4 mm²
Mounting	Screw in

DIMENSIONS

Length	15.5 mm
Width	5.3 mm
Height	11.7 mm

CONNECTION DATA

Cross section single wire from	0.5 mm²
Cross section single wire to	4 mm²
Cross section stranded wire from	5 mm²
Cross section stranded wire to	4 mm²
Stripping length	16 mm

Screw type	Slotted

MATERIALS

Insulation material	Polyamide 6.6
Flammability class	UL94-V2
Operating temperature from	-40 °C
Operating temperature to	105 °C

ADDITIONAL DATA

Tariff code	85369010
Country of origin	DE
Weight	3.02 g
Pack size	50