


BUSBAR CLAMPING YOKE TERMINALS - ZB SERIES

ZB, SSCH

2483.5

ZB 4/K Blue, 4mm² clamping yoke for 10 x 3 busbar

- Screw couplings
- Clamp sizes, 4mm², 16mm² or 35mm²
- Available for 10x3mm or 6x6mm bar
- Material polyamide 6.6 - UL94-V2



PRODUCT DESCRIPTION

Busbars and clamping yokes

The ZB clamping yoke can be used in conjunction with the 10 x 3 or 6 x 6 busbars in order to bring the neutral conductor or Earth (PE) conductor together at one point.

The SH and ES busbar supports are used to mount the busbar, either directly to the back plate or on the DIN rail. With longer rails, these can be positioned between the clamping yokes to give extra support.

The clamping yokes are available with or without insulating caps, green/yellow as a PE connection, blue for Neutral and Black.

These caps together with the labelling tags help the connections wires to be clearly assigned.

TECHNICAL DATA

GENERAL DATA

| | |
|--------------------------|-------------------|
| Rated wire cross section | 4 mm ² |
| Colour | Blue |
| Mounting | Screw in |

DIMENSIONS

| | |
|--------|---------|
| Length | 15.5 mm |
| Width | 5.3 mm |
| Height | 11.7 mm |

CONNECTION DATA

| | |
|----------------------------------|---------------------|
| Cross section single wire from | 0.5 mm ² |
| Cross section single wire to | 4 mm ² |
| Cross section stranded wire from | 0.5 mm ² |

| | |
|--------------------------------|-------------------|
| Cross section stranded wire to | 4 mm ² |
| Stripping length | 16 mm |
| Screw type | Slotted |

MATERIALS

| | |
|----------------------------|---------------|
| Insulation material | Polyamide 6.6 |
| Flammability class | UL94-V2 |
| Operating temperature from | -40 °C |
| Operating temperature to | 105 °C |

ADDITIONAL DATA

| | |
|-------------------|----------|
| Tariff code | 85369010 |
| Country of origin | DE |
| Weight | 3.6 g |
| Pack size | 50 |