


BUSBAR CLAMPING YOKE TERMINALS - ZB SERIES

ZB, SSCH

2485.1

ZB 35/K Green/Yellow, 35mm² clamping yoke for 10 x 3 busbar



- Screw couplings
- Clamp sizes, 4mm², 16mm² or 35mm²
- Available for 10x3mm or 6x6mm bar
- Material polyamide 6.6 - UL94-V2

PRODUCT DESCRIPTION

Busbars and clamping yokes

The ZB clamping yoke can be used in conjunction with the 10 x 3 or 6 x 6 busbars in order to bring the neutral conductor or Earth (PE) conductor together at one point.

The SH and ES busbar supports are used to mount the busbar, either directly to the back plate or on the DIN rail. With longer rails, these can be positioned between the clamping yokes to give extra support.

The clamping yokes are available with or without insulating caps, green/yellow as a PE connection, blue for Neutral and Black.

These caps together with the labelling tags help the connections wires to be clearly assigned.

TECHNICAL DATA

GENERAL DATA

Rated wire cross section	35 mm ²
Colour	Green/yellow
Mounting	Screw in

DIMENSIONS

Length	18 mm
Width	14 mm
Height	21 mm

CONNECTION DATA

Cross section single wire from	16 mm ²
Cross section single wire to	35 mm ²
Cross section stranded wire from	16 mm ²

Cross section stranded wire to	35 mm ²
Stripping length	18 mm
Screw type	Slotted

MATERIALS

Insulation material	Polyamide 6.6
Flammability class	UL94-V2
Operating temperature from	-40 °C
Operating temperature to	105 °C

ADDITIONAL DATA

Tariff code	85369010
Country of origin	DE
Weight	18.75 g
Pack size	20