

## EXTERNAL LINK CROSS CONNECTORS

### AQI External Links

2028.0

AQI 4/5/15 - 4 pole External Cross connector for  
RK2.5/ZSRK2.5/ZRK2.5/ZRKD2.5/ZIKD2.5/ZTRK2.5/ZI  
ZA1.5/SRK2.52A

- Insulated for protection
- Reliable & secure fixing



### PRODUCT DESCRIPTION

External cross connection links makes it possible to connect potentials of terminals where there is no option of a central cross connection channel.

These links are quicker, easier and a more reliable way of linking than using wire links with ferrules.

When using the external, the rated cross section of wire is reduced to the next smallest size.

## TECHNICAL DATA

### GENERAL DATA

Colour	Yellow
Rated current IEC	27 A
Mounting	Push in
Contamination degree	3
Additional information	for RK 2,5   RK 2,5/35 N/2Q

### DIMENSIONS

Width	19.46 mm
Pitch	5 mm

### CONNECTION DATA

Number of poles	4
-----------------	---

### MATERIALS

Material	Copper
Insulation material	Polyamide 6.6

Flammability class	UL94-V2
Operating temperature from	-40 °C
Operating temperature to	105 °C

**ADDITIONAL DATA**

Tariff code	85369010
Country of origin	DE
Weight	1.36 g
Pack size	50