

EXTERNAL LINK CROSS CONNECTORS

AQI External Links

2029.0

AQI 10/5/15 - 10 pole External Cross connector for
RK2.5/ZSRK2.5/ZRK2.5/ZRKD2.5/ZIKD2.5/ZTRK2.5/ZI
ZA1.5/SRK2.52A

- Insulated for protection
- Reliable & secure fixing



PRODUCT DESCRIPTION

External cross connection links makes it possible to connect potentials of terminals where there is no option of a central cross connection channel.

These links are quicker, easier and a more reliable way of linking than using wire links with ferrules.

When using the external, the rated cross section of wire is reduced to the next smallest size.

TECHNICAL DATA

GENERAL DATA

| | |
|------------------------|-----------------------------|
| Colour | Yellow |
| Rated current IEC | 27 A |
| Mounting | Push in |
| Contamination degree | 3 |
| Additional information | for RK 2,5 RK 2,5/35 N/2Q |

DIMENSIONS

| | |
|-------|---------|
| Width | 50.1 mm |
| Pitch | 5 mm |

CONNECTION DATA

| | |
|-----------------|----|
| Number of poles | 10 |
|-----------------|----|

MATERIALS

| | |
|---------------------|---------------|
| Material | Copper |
| Insulation material | Polyamide 6.6 |

| | |
|----------------------------|---------|
| Flammability class | UL94-V2 |
| Operating temperature from | -40 °C |
| Operating temperature to | 105 °C |

ADDITIONAL DATA

| | |
|-------------------|----------|
| Tariff code | 85369010 |
| Country of origin | DE |
| Weight | 3.5 g |
| Pack size | 10 |