OEM AUTOMATIC

OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

CONTACLIP

CROSS CONNECTORS FOR SRK, SSL & SRKD RANGE

SQI, SQ

17252.8
SQI 35/2 YE - 2 Way Cross Connector for SRK/SSL 35/2A

- For SRK 2.5-120mm²
- Insulated plug in up to 35mm²
- Fully rated
- Can be cut down with insulated cap. No partition required
- Screw in 50-120mm²

PRODUCT DESCRIPTION

TECHNICAL DATA

GENERAL DATA

Rated wire cross section	35 mm²
Colour	Yellow
Voltage max	1000 V
Rated current IEC	125 A
Load current max	150 A
Mounting	Push in
Contamination degree	3

DIMENSIONS

Length	6.2 mm
Width	26.5 mm
Pitch	16 mm

CONNECTION DATA

Number of poles	2

MATERIALS

Material	Bronze
Insulation material	Polyamide 6.6
Flammability class	UL94-V2
Operating temperature from	-40 °C
Operating temperature to	105 °C

ADDITIONAL DATA

Tariff code	85369010
Country of origin	DE
Weight	14 g
Pack size	20