OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

CROSS CONNECTORS FOR SRK, SSL & SRKD RANGE

Cross Connectors for Screw Terminals - SQI, SQ

17265.0
SQ 70/2, 2 pole cross connector for SRK70



- For SRK 2.5-120mm²
- Insulated plug in up to 35mm²
- Fully rated
- Can be cut down with insulated cap. No partition required (up to 10mm)
- Screw in 50-120mm²

PRODUCT DESCRIPTION

The SQI and SQ cross-connectors are insulated plug-in bridging links designed for use with CONTA-CLIP's SRK feed-through terminals, SSL protective-earth terminals, and the double-level SRKD/SSLD variants. They are available in lengths accommodating 2 to 10 poles and a longer 30-pole version, suitable for terminal cross-sections from 2.5 mm² up to 120 mm². These fully rated connectors allow potential distribution (short-circuit bridging or daisy-chaining) along a row of DIN-rail mounted terminals. They can be trimmed to length as needed and capped with yellow SQIK insulating end-caps to restore touch protection after cutting. No additional partition walls are required between bridged terminals. All insulating parts meet UL 94 V-0 rated polyamide specifications and commonly support conductor cross-sections up to 35 mm² for the plug-in portion.
These cross-connectors greatly streamline wiring in industrial control panels, energy distribution boards, machine automation systems, and infrastructure installations. Instead of manually wiring each terminal, similar potentials (e.g. common ground or signal lines) can be reliably shared across multiple points with a simple plug-in bridge, saving time and reducing wiring errors. They are especially popular in factory automation, process engineering, transportation control cabinets, and building infrastructure systems. The ability to cut them to exact length and cap the exposed ends adds flexibility for custom configurations, while maintaining electrical safety and compliance. Their compatibility with both single- and double-deck SRK/SSL/SRKD modules ensures scalable installation designs across conductor sizes and system layouts.

TECHNICAL DATA

GENERAL DATA

Rated wire cross section	70 mm²
Voltage max	1000 V
Rated current IEC	192 A
Load current max	232 A
Mounting	Screw in
Contamination degree	3
Additional information	for SRK 70

DIMENSIONS

Length	10 mm
Width	34.3 mm
Distance to hole centres	20.5 mm
Pitch	20.5 mm
Hole diameter	5.5 mm

CONNECTION DATA

Number of poles	2
Screw size	M 6
Screw type	Slotted
Torque min	3.2
Torque max	3.7

MATERIALS

Material	Copper

ADDITIONAL DATA

Tariff code	85369010
Country of origin	DE
Weight	37.82 g
Pack size	10