

**CROSS CONNECTORS FOR SRK, SSL & SRKD RANGE**

SQI, SQ

17278.0  
SQ 120/2, 2 pole cross connector for SRK120

- For SRK 2.5-120mm<sup>2</sup>
- Insulated plug in up to 35mm<sup>2</sup>
- Fully rated
- Can be cut down with insulated cap. No partition required
- Screw in 50-120mm<sup>2</sup>

**PRODUCT DESCRIPTION****TECHNICAL DATA****GENERAL DATA**

Rated wire cross section	120 mm <sup>2</sup>
Voltage max	1000 V
Rated current IEC	269 A
Load current max	290 A
Mounting	Screw in
Contamination degree	3
Additional information	for SRK 120

**DIMENSIONS**

Length	10 mm
Width	44 mm
Distance to hole centres	27 mm
Pitch	27 mm
Hole diameter	5.5 mm

**CONNECTION DATA**

<b>Number of poles</b>	2
<b>Screw size</b>	M 6
<b>Screw type</b>	Slotted
<b>Torque min</b>	3.2
<b>Torque max</b>	3.7

## **MATERIALS**

<b>Material</b>	Copper
-----------------	--------

## **ADDITIONAL DATA**

<b>Tariff code</b>	85369010
<b>Country of origin</b>	DE
<b>Weight</b>	64.92 g
<b>Pack size</b>	10