

0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk


CONTACLIP

EXTERNAL LINK CROSS CONNECTORS

AQI External Links

3445.8 AQI 60/8/11 - 60 pole External Cross connector for STK1/STK2/STKD1/BKA10

- Insulated for protection
- Reliable & secure fixing



PRODUCT DESCRIPTION

External cross connection links makes it possible to connect potentials of terminals where there is no option of a central cross connection channel.

These links are quicker, easier and a more reliable way of linking than using wire links with ferrules.

When using the external, the rated cross section of wire is reduced to the next smallest size.

TECHNICAL DATA

GENERAL DATA

Rated current IEC 57 A Mounting Push in Contamination degree 3	Colour Yell	DW .
Contamination degree 3	Rated current IEC 57 A	
	flounting Pus	n in
	Contamination degree 3	
Additional information for BKA 10 STK 1 STK 2 STKD 1	Additional information for E	3KA 10 STK 1 STK 2 STKD 1

DIMENSIONS

Pitch	8 mm

CONNECTION DATA

Number of poles 60

MATERIALS

Material	Соррег
Insulation material	Polyamide 6.6
Flammability class	UL94-V2

Operating temperature from	-40 °C
Operating temperature to	105 °C

ADDITIONAL DATA

Tariff code	85369010
Country of origin	DE
Weight	50 g
Pack size	1