OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

CROSS CONNECTORS FOR PRK, PSL, PRKD, PPVK, PTKS RANGE

Push In Terminal Cross Connectors - PQI

27085.9
PQI 4/3/PTKS Red, 3 Way Cross Coonector for PTKS 4



- Fully rated for the matching terminal
- Plug in for fast and easy connection
- Pins can be removed for jumping terminals

PRODUCT DESCRIPTION

The PQI pluggable cross-connectors helps you to save time while distributing potentials over terminal blocks of similar or different cross-section ranges.
The pluggable design of the PQI offers the advantage that it can carry the full rated current even while operating at the fully rated voltage.
The PQI is insulated to protect against accidental touch and is available in the cross-section range from 1.5 mm² to 10 mm² in 2-, 3-, 4-, 10- and 20-pole versions and 2 way for 16mm² terminals.
Standard colour is Red, but Blue & Black are also available.

TECHNICAL DATA

GENERAL DATA

Colour	Red
Rated cross section	4 mm²
Rated current	32 A
Voltage max	800 V
Load current max	32 A
Contamination degree	3

CONNECTION DATA

Number of poles	3

MATERIALS

Material	Polyamide 6.6
Insulation material	Polyamide 6.6
Flammability class	V-0

Operating temperature from	-40 °C
Operating temperature to	120 °C

ADDITIONAL DATA

Tariff code	85369010
Country of origin	DE
Pack size	50















