OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

I SERIES, PANEL MOUNT BEACON, Ø65, Ø45 AND Ø30MM

801512313
Panel mount xenon strobe, Ø45mm, Red, 230-240 V ac, ISM

- Ø65, Ø45 and Ø30mm Panel mount beacons
- Strobe, Flashing and Steady LED options
- Wide control voltage range



PRODUCT DESCRIPTION

The I series offers a high quality, bright, panel mounted beacon. The units can be single or dual colour, have multiple colour and voltage options and in the case of IMM/IMM can be pre-cable with IP67 Protection.

The comprehensive M22 built-in signal device series is available in three sizes Ø 30 mm, Ø 45 mm und Ø 65 mm. The high luminosity and signal effect is seen all around due to the calotte. The beacon is extremely durable and vibration-resistant, with a high degree of protection of IP65 and IP67 for prewired models. The I Series range can come with a demountable plug in terminal or individually prewired.

A complete range of LED steady/flashing/strobe and multi colour models for versatile applications in the industry, enclosures, etc. It is maintenance free, offers a low current consumption, long life time, shock and vibration-proof. Multi colour models are also available in 6 LED colours individually selectable.
Housing and lenses made of impact resistant polycarbonate, housing colour black or grey.

TECHNICAL DATA

GENERAL DATA

Lens colour	Red
Light type	Strobe
Light source	Xenon
Housing Colour	Black
Mounting	Panel mount

RATED OPERATING CONDITIONS

Nominal Supply Voltage	230-240 V AC
Nominal current	12 mA
Flash energy	0.5 J
Flash frequency	1.4 Hz

Operational temperature	-25°C ... 60°C
Terminal connection	2.5 mm²

DIMENSIONS

Height	76 mm
Diameter	45 mm

ADDITIONAL DATA

IP class	IP65



