



I SERIES, PANEL MOUNT BEACON, Ø65, Ø45 AND Ø30MM

802502405

Panel mount LED Beacon, Ø65mm, Red, 24 V ac/dc, IBL

- Ø65, Ø45 and Ø30mm Panel mount beacons
- Strobe, Flashing and Steady LED options
- Wide control voltage range



PRODUCT DESCRIPTION

The I series offers a high quality, bright, panel mounted beacon. The units can be single or dual colour, have multiple colour and voltage options and in the case of IMM/IMM can be pre-cable with IP67 Protection.

The comprehensive M22 built-in signal device series is available in three sizes Ø 30 mm, Ø 45 mm und Ø 65 mm. The high luminosity and signal effect is seen all around due to the calotte. The beacon is extremely durable and vibration-resistant, with a high degree of protection of IP65 and IP67 for prewired models. The I Series range can come with a demountable plug in terminal or individually prewired.

A complete range of LED steady/flashing/strobe and multi colour models for versatile applications in the industry, enclosures, etc. It is maintenance free, offers a low current consumption, long life time, shock and vibration-proof. Multi colour models are also available in 6 LED colours individually selectable. Housing and lenses made of impact resistant polycarbonate, housing colour black or grey.

TECHNICAL DATA

GENERAL DATA

| | |
|----------------|------------------|
| Lens colour | Red |
| Light type | Flashing, Steady |
| Light source | LED |
| Housing Colour | Black |
| Mounting | Panel mount |

RATED OPERATING CONDITIONS

| | |
|------------------------|------------|
| Nominal Supply Voltage | 24 V AC/DC |
| Nominal current | 60 mA |
| Flash frequency | 2 Hz |

| | |
|-------------------------|---------------------|
| Operational temperature | -25°C ... 60°C |
| Terminal connection | 2.5 mm ² |

DIMENSIONS

| | |
|----------|-------|
| Height | 90 mm |
| Diameter | 65 mm |
| Weight | 75 g |

ADDITIONAL DATA

| | |
|----------|------|
| IP class | IP65 |
|----------|------|

