



## I SERIES, PANEL MOUNT BEACON, Ø65, Ø45 AND Ø30MM

802517313

Panel mount xenon strobe, Ø65mm, Yellow, 230-240 V ac, ISL

- Ø65, Ø45 and Ø30mm Panel mount beacons
- Strobe, Flashing and Steady LED options
- Wide control voltage range



### PRODUCT DESCRIPTION

The I series offers a high quality, bright, panel mounted beacon. The units can be single or dual colour, have multiple colour and voltage options and in the case of IMM/IMM can be pre-cable with IP67 Protection.

The comprehensive M22 built-in signal device series is available in three sizes Ø 30 mm, Ø 45 mm und Ø 65 mm. The high luminosity and signal effect is seen all around due to the calotte. The beacon is extremely durable and vibration-resistant, with a high degree of protection of IP65 and IP67 for prewired models. The I Series range can come with a demountable plug in terminal or individually prewired.

A complete range of LED steady/flashing/strobe and multi colour models for versatile applications in the industry, enclosures, etc. It is maintenance free, offers a low current consumption, long life time, shock and vibration-proof. Multi colour models are also available in 6 LED colours individually selectable. Housing and lenses made of impact resistant polycarbonate, housing colour black or grey.

## TECHNICAL DATA

### GENERAL DATA

|                |             |
|----------------|-------------|
| Lens colour    | Yellow      |
| Light type     | Strobe      |
| Light source   | Xenon       |
| Housing Colour | Black       |
| Mounting       | Panel mount |

### RATED OPERATING CONDITIONS

|                        |              |
|------------------------|--------------|
| Nominal Supply Voltage | 230-240 V AC |
| Nominal current        | 20 mA        |

|                         |                     |
|-------------------------|---------------------|
| Flash energy            | 1 J                 |
| Flash frequency         | 1.4 Hz              |
| Operational temperature | -25°C ... 60°C      |
| Terminal connection     | 2.5 mm <sup>2</sup> |

DIMENSIONS

|          |       |
|----------|-------|
| Height   | 90 mm |
| Diameter | 65 mm |

ADDITIONAL DATA

|          |      |
|----------|------|
| IP class | IP65 |
|----------|------|

ISL / ISM / ISS

|    |   |    |
|----|---|----|
| La | N | Lb |
| X  | X |    |

