

OEM Automatic Ltd

Address: Whiteacres, Whetstone Leicester, LE8 6ZG 0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

G SERIES, WARNING LIGHT Ø120 MM

822507900 Steady beacon, Ø120mm, Yellow, WLG



- Fixed or flashing shine
- Max. 25 W
- IP65
- · Bayonet connector



PRODUCT DESCRIPTION

The Series G is AUERs best-value solution for universal applications. The large signal lamp with 48 LEDs produces an excellent frontal and lateral signal effect. The surface-mounted beacon series is available in the size Ø 120 mm with a low calotte. With an ingress protection class of IP65, the G series surface-mounted beacon is recommended for outdoor use.

Mounting options include vertical mounting, this model also contains a bayonet locking system with push button. It is used for general applications due to its attractive price to performance ratio.

TECHNICAL DATA

GENERAL DATA

Lens colour	Yellow
Light type	Steady
Light source	Bulb
Housing Colour	Black
Lamp socket	Ba15d
Number of optional modules	1

RATED OPERATING CONDITIONS

Nominal Supply Voltage	12-24 V
Lamp power	25 W
Operational temperature	-30°C 60°C

Terminal connection	2.5 mm ²	
DIMENSIONS		
Height	102 mm	
Diameter	120 mm	
Weight	230 g	

ADDITIONAL DATA

IP class	IP65

















