

0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

## Q SERIES, CUBIC BEACON, 94MM, 132MM OR 184MM

874667408 Xenon strobe, 132mm, Yellow, 24-48 V ac/dc, QFM

- 94mm, 132mm or 184mm Cubic beacon
- Steady, Flashing, Strobe and Multi-strobe light options
- Wide control voltage range



#### **PRODUCT DESCRIPTION**

The Q series is the largest and most comprehensive beacon series in four sizes with a square design. The extensive product range is available in 94 mm, 132 mm, 184 mm and 228 mm sizes and is available with state-of-the-art LED or xenon technology.

The Q series offers a long lifetime, low current consumption and is vibration proof. The LED steady/flashing beacons are available in all sizes and the LED multi strobe beacons in 184mm and 228mm. It is also available in conventional xenon strobe technique This unique range includes LED technique with high signalling effect 3 strobe patterns (double/6 times/multi strobe) and externally switchable.

For applications in the industry, process control, fire/gas alarm, marine, and is also fit for plc applications (leakage, inrush current)

Luminaires of the LED series boast a particularly high luminous intensity of up to 400 candela thanks to special high-power LEDs. The unique calotte design gives the signal effect both frontally and laterally. The calottes of the Q series are available in six different colours and are made of highly impact-resistant polycarbonate, which is UV-stabilised and guarantees colour fastness even under extreme conditions. With a protection class of IP66 and an impact resistance of IK09, the Q series is suitable for industrial, processing and marine applications.

# **TECHNICAL DATA**


### **GENERAL DATA**


Lens colour	Yellow
Light type	Strobe
Light source	Xenon
Housing Colour	Red

## **RATED OPERATING CONDITIONS**

Nominal Supply Voltage	24-48 V AC/DC
Nominal current	900 mA
Flash energy	10 J

Flash frequency	1 Hz
Operational temperature	-30°C 60°C
Terminal connection	2.5 mm <sup>2</sup>
DIMENSIONS	
Height	138 mm
Diameter	132 mm
ADDITIONAL DATA	
IP class	IP66
IK class	9





	A	8	с	D	ε	F	G	н	1	J	к	L	M	N	0	Р
Size 2	143	95	10	32	50	36,6	81,5	11,5	57,4	136,8	206,8	6,5	91	131,8	91	131,8
Size 3	199	112	16	48	70	66	105,5	18,5	72,5	175,8	262,8	6,5	124	183,5	124	183,5
Size 4	243,3	140	10	70	100	63	133,3	16,8	90,8	223,4	340	167	228,4	167	228,4	6,5