OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

# I SERIES, PANEL MOUNT BEACON, Ø65, Ø45 AND Ø30MM

802502313
Panel mount LED Beacon, Ø65mm, Red, 230-240 V ac, IBL

- Ø65, Ø45 and Ø30mm Panel mount beacons
- Strobe, Flashing and Steady LED options
- Wide control voltage range



### PRODUCT DESCRIPTION

The I series offers a high quality, bright, panel mounted beacon. The units can be single or dual colour, have multiple colour and voltage options and in the case of IMM/IMM can be pre-cable with IP67 Protection.

The comprehensive M22 built-in signal device series is available in three sizes Ø 30 mm, Ø 45 mm und Ø 65 mm. The high luminosity and signal effect is seen all around due to the calotte. The beacon is extremely durable and vibration-resistant, with a high degree of protection of IP65 and IP67 for prewired models. The I Series range can come with a demountable plug in terminal or individually prewired.

A complete range of LED steady/flashing/strobe and multi colour models for versatile applications in the industry, enclosures, etc. It is maintenance free, offers a low current consumption, long life time, shock and vibration-proof. Multi colour models are also available in 6 LED colours individually selectable.
Housing and lenses made of impact resistant polycarbonate, housing colour black or grey.

# TECHNICAL DATA

## GENERAL DATA

| | |
|---|---|
| **Lens colour** | Red |
| **Light type** | Flashing, Steady |
| **Light source** | LED |
| **Housing Colour** | Black |
| **Mounting** | Panel mount |

## RATED OPERATING CONDITIONS

| | |
|---|---|
| **Nominal Supply Voltage** | 230-240 V AC |
| **Nominal current** | 31 mA |
| **Flash frequency** | 2 Hz |
| **Operational temperature** | -25°C ... 60°C |

| | |
|---|---|
| **Terminal connection** | 2.5 mm² |

## DIMENSIONS

| | |
|---|---|
| **Height** | 90 mm |
| **Diameter** | 65 mm |
| **Weight** | 75 g |

## ADDITIONAL DATA

| | |
|---|---|
| **IP class** | IP65 |

