OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

# T SERIES, MODULAR BEACON, Ø75MM

859504405
LED Steady/flashing, Ø75mm, Clear, 24 V ac/dc, TDC



- Ø75mm Modular beacon
- Steady, flashing and Multi-strobe light options
- Wide control voltage range

### PRODUCT DESCRIPTION

AUERs T Series range begins with a Ø 75 mm large comprehensive modular beacon range, the design is modern, efficient with long-life LED beacons in functions. Settings include LED steady/flashing which are both externally addressable and LED multi strobe, both strobe patterns, which are 6 times fast strobe and multi strobe, are again externally addressable.

Also including a steady beacon option with BA15d socket for 7 W incandescent bulb, the T Series can be used for a range of applications involving industrial and general applications. It is fir for plc applications like leakage and inrush current. And has a UL type of 4/4X/13 (excluding TNL and TMW+TVS).

There are also optionally available protective vents for pressure balance in harsh weather conditions (humidity, high temperature fluctuations, etc.) for TMW, TMF, TNL. A comprehensive range of selectable mounting options, and an Ingress protection of IP66.

# TECHNICAL DATA

## GENERAL DATA

| | |
|---|---|
| **Lens colour** | Clear |
| **Light type** | Flashing, Steady |
| **Light source** | LED |
| **Mounting** | Bayonet |

## RATED OPERATING CONDITIONS

| | |
|---|---|
| **Nominal Supply Voltage** | 24 V AC/DC |
| **Nominal current** | 220 mA |
| **Flash frequency** | 2 Hz |
| **Operational temperature** | -30°C ... 60°C |

| | |
|---|---|
| **Terminal connection** | 2.5 mm² |

## DIMENSIONS

| | |
|---|---|
| **Height** | 75 mm |
| **Diameter** | 75 mm |
| **Weight** | 86 g |

## ADDITIONAL DATA

| | |
|---|---|
| **IP class** | IP66 |
| **IK class** | 8 |



