OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

T SERIES, MODULAR BEACON, Ø75MM

859511310
LED Multi-strobe, Ø75mm, Amber, 110-120 V ac, TDF



- Ø75mm Modular beacon
- Steady, flashing and Multi-strobe light options
- Wide control voltage range

PRODUCT DESCRIPTION

AUERs T Series range begins with a Ø 75 mm large comprehensive modular beacon range, the design is modern, efficient with long-life LED beacons in functions. Settings include LED steady/flashing which are both externally addressable and LED multi strobe, both strobe patterns, which are 6 times fast strobe and multi strobe, are again externally addressable.

Also including a steady beacon option with BA15d socket for 7 W incandescent bulb, the T Series can be used for a range of applications involving industrial and general applications. It is fir for plc applications like leakage and inrush current. And has a UL type of 4/4X/13 (excluding TNL and TMW+TVS).

There are also optionally available protective vents for pressure balance in harsh weather conditions (humidity, high temperature fluctuations, etc.) for TMW, TMF, TNL. A comprehensive range of selectable mounting options, and an Ingress protection of IP66.

TECHNICAL DATA

GENERAL DATA

Lens colour	Orange
Light type	Multi strobe
Light source	LED
Mounting	Bayonet

RATED OPERATING CONDITIONS

Nominal Supply Voltage	110-120 V AC
Nominal current	42 mA
Flash frequency	1 Hz
Operational temperature	-30°C ... 60°C

Terminal connection	2.5 mm²

DIMENSIONS

Height	75 mm
Diameter	75 mm
Weight	86 g

ADDITIONAL DATA

IP class	IP66
IK class	8



