



## U SERIES, MODULAR BEACON, Ø60M

858504405

LED Steady/flashing beacon, Ø60mm, Clear, 24 V  
ac/dc, UDC

- Ø60mm, Modular beacon
- Steady, Flashing and Multi-strobe light options
- Wide control voltage range



### PRODUCT DESCRIPTION

AUER's U Series range begins with a Ø 65 mm comprehensive modular beacon range, the design is modern, efficient with long-life LED beacons in functions. Settings include LED steady/flashing which are both externally addressable and LED multi strobe, both strobe patterns, which are 6 times fast strobe and multi strobe, are again externally addressable.

Also including a Steady beacon option with base integrated BA15d socket for 4 W incandescent bulb, the U Series can be used for a range of applications involving industrial and general applications. It is fit for plc applications like leakage and inrush current. And has a UL type of 4/4X/13.

## TECHNICAL DATA

### GENERAL DATA

Lens colour	White
Light type	Flashing, Steady
Light source	LED
Mounting	Bayonet
Number of optional modules	1

### RATED OPERATING CONDITIONS

Nominal Supply Voltage	24 V AC/DC
Nominal current	100 mA
Flash frequency	2 Hz
Operational temperature	-30°C ... 60°C

Terminal connection	2.5 mm <sup>2</sup>
---------------------	---------------------

## DIMENSIONS

Height	58 mm
Diameter	60 mm
Weight	52 g

## ADDITIONAL DATA

IP class	IP66
IK class	8

