



## U SERIES, MODULAR BEACON, Ø60M

858507310

LED Steady/flashing beacon, Ø60mm, Yellow, 110-120

V ac, UDC

- Ø60mm, Modular beacon
- Steady, Flashing and Multi-strobe light options
- Wide control voltage range



### PRODUCT DESCRIPTION

AUER's U Series range begins with a Ø 65 mm comprehensive modular beacon range, the design is modern, efficient with long-life LED beacons in functions. Settings include LED steady/flashing which are both externally addressable and LED multi strobe, both strobe patterns, which are 6 times fast strobe and multi strobe, are again externally addressable.

Also including a Steady beacon option with base integrated BA15d socket for 4 W incandescent bulb, the U Series can be used for a range of applications involving industrial and general applications. It is fit for plc applications like leakage and inrush current. And has a UL type of 4/4X/13.

## TECHNICAL DATA

### GENERAL DATA

|                            |                  |
|----------------------------|------------------|
| Lens colour                | Yellow           |
| Light type                 | Flashing, Steady |
| Light source               | LED              |
| Mounting                   | Bayonet          |
| Number of optional modules | 1                |

### RATED OPERATING CONDITIONS

|                         |                |
|-------------------------|----------------|
| Nominal Supply Voltage  | 110-120 V AC   |
| Nominal current         | 45 mA          |
| Flash frequency         | 2 Hz           |
| Operational temperature | -30°C ... 60°C |

|                     |                     |
|---------------------|---------------------|
| Terminal connection | 2.5 mm <sup>2</sup> |
|---------------------|---------------------|

## DIMENSIONS

|          |       |
|----------|-------|
| Height   | 58 mm |
| Diameter | 60 mm |
| Weight   | 52 g  |

## ADDITIONAL DATA

|          |      |
|----------|------|
| IP class | IP66 |
| IK class | 8    |

