OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

U SERIES, MODULAR BEACON, Ø60M

858512405
LED Multi-strobe beacon, Ø60mm, Red, 24 V ac/dc, UDF



- Ø60mm, Modular beacon
- Steady, Flashing and Multi-strobe light options
- Wide control voltage range

PRODUCT DESCRIPTION

AUERs U Series range begins with a Ø 65 mm comprehensive modular beacon range, the design is modern, efficient with long-life LED beacons in functions. Settings include LED steady/flashing which are both externally addressable and LED multi strobe, both strobe patterns, which are 6 times fast strobe and multi strobe, are again externally addressable.

Also including a Steady beacon option with base integrated BA15d socket for 4 W incandescent bulb, the U Series can be used for a range of applications involving industrial and general applications. It is fir for plc applications like leakage and inrush current. And has a UL type of 4/4X/13.

TECHNICAL DATA

GENERAL DATA

Lens colour	Red
Light type	Multi strobe
Light source	LED
Mounting	Bayonet
Number of optional modules	1

RATED OPERATING CONDITIONS

Nominal Supply Voltage	24 V AC/DC
Nominal current	120 mA
Flash frequency	1 Hz
Operational temperature	-30°C ... 60°C
Terminal connection	2.5 mm²

DIMENSIONS

Height	58 mm
Diameter	60 mm
Weight	52 g

ADDITIONAL DATA

IP class	IP66
IK class	8

