OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

# U SERIES, MODULAR BEACON, Ø60M

858514310
LED Multi-strobe beacon, Ø60mm, Clear, 110-120 V ac, UDF



- Ø60mm, Modular beacon
- Steady, Flashing and Multi-strobe light options
- Wide control voltage range

### PRODUCT DESCRIPTION

AUERs U Series range begins with a Ø 65 mm comprehensive modular beacon range, the design is modern, efficient with long-life LED beacons in functions. Settings include LED steady/flashing which are both externally addressable and LED multi strobe, both strobe patterns, which are 6 times fast strobe and multi strobe, are again externally addressable.

Also including a Steady beacon option with base integrated BA15d socket for 4 W incandescent bulb, the U Series can be used for a range of applications involving industrial and general applications. It is fir for plc applications like leakage and inrush current. And has a UL type of 4/4X/13.

# TECHNICAL DATA

## GENERAL DATA

| | |
|---|---|
| **Lens colour** | White |
| **Light type** | Multi strobe |
| **Light source** | LED |
| **Mounting** | Bayonet |
| **Number of optional modules** | 1 |

## RATED OPERATING CONDITIONS

| | |
|---|---|
| **Nominal Supply Voltage** | 110-120 V AC |
| **Nominal current** | 33 mA |
| **Flash frequency** | 1 Hz |
| **Operational temperature** | -30°C ... 60°C |
| **Terminal connection** | 2.5 mm² |

## DIMENSIONS

| | |
|---|---|
| **Height** | 58 mm |
| **Diameter** | 60 mm |
| **Weight** | 52 g |

## ADDITIONAL DATA

| | |
|---|---|
| **IP class** | IP66 |
| **IK class** | 8 |

