



U SERIES, MODULAR BEACON, Ø60M

858515310

LED Multi-strobe beacon, Ø60mm, Blue, 110-120 V ac,
UDF

- Ø60mm, Modular beacon
- Steady, Flashing and Multi-strobe light options
- Wide control voltage range



PRODUCT DESCRIPTION

AUER's U Series range begins with a Ø 65 mm comprehensive modular beacon range, the design is modern, efficient with long-life LED beacons in functions. Settings include LED steady/flashing which are both externally addressable and LED multi strobe, both strobe patterns, which are 6 times fast strobe and multi strobe, are again externally addressable.

Also including a Steady beacon option with base integrated BA15d socket for 4 W incandescent bulb, the U Series can be used for a range of applications involving industrial and general applications. It is fit for plc applications like leakage and inrush current. And has a UL type of 4/4X/13.

TECHNICAL DATA

GENERAL DATA

| | |
|----------------------------|--------------|
| Lens colour | Blue |
| Light type | Multi strobe |
| Light source | LED |
| Mounting | Bayonet |
| Number of optional modules | 1 |

RATED OPERATING CONDITIONS

| | |
|-------------------------|----------------|
| Nominal Supply Voltage | 110-120 V AC |
| Nominal current | 33 mA |
| Flash frequency | 1 Hz |
| Operational temperature | -30°C ... 60°C |

| | |
|---------------------|---------------------|
| Terminal connection | 2.5 mm ² |
|---------------------|---------------------|

DIMENSIONS

| | |
|----------|-------|
| Height | 58 mm |
| Diameter | 60 mm |
| Weight | 52 g |

ADDITIONAL DATA

| | |
|----------|------|
| IP class | IP66 |
| IK class | 8 |

