OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

AUER SIGNAL SERIES 50 SMART DOT BEACON

SD50-GYR and SD50-MC7

SD50-GR
SD5B2 Smart Dot 50 Basic Beacon Green/Red



- High brightness, colour brilliance and energy efficiency
- Excellent homogeneous and flexible colour signalling
- Multiple animation modes
- Smart Protection
- IP66, IP67, IP69, IP69K and IP6K9K, and an impact resistance of IK08

PRODUCT DESCRIPTION

The **Smart Dot 50** from **Auer Signal** is a high-performance signal light developed for machine panels, automation systems, and demanding industrial environments where clear, reliable status indication is essential.
Available in three- or seven-colour versions, the Smart Dot 50 offers versatile lighting modes to suit a wide range of applications. The standardized M12 5-pin connector ensures fast, safe installation—reducing wiring time, minimizing downtime, and simplifying integration into existing systems.
Delivering up to four times the brightness of comparable products, the Smart Dot 50 guarantees excellent visibility even in bright ambient conditions. Its superior color rendering ensures clear signal recognition, while energy-efficient LED technology keeps power consumption low—making it ideal for applications where efficiency matters.
Intelligent power management actively controls and limits inrush current, protecting PLC outputs and sensitive electronics from unnecessary stress. Integrated temperature monitoring regulates operation to prevent overheating, extending service life and enhancing operational reliability. The unit is also designed to withstand high leakage currents, ensuring dependable performance in complex or interference-prone electrical systems.

With its compact footprint, robust construction, and advanced functionality, the Auer Smart Dot 50 is suitable for a broad range of industries—from machine building and intralogistics to automotive manufacturing and building automation. Engineered for durability and performance, it delivers reliable signaling even in the most demanding environments.

TECHNICAL DATA

GENERAL DATA

Lens colour	White
Light type	Green LED, Red LED
Light source	LED
Housing Colour	Black

RATED OPERATING CONDITIONS

Nominal Supply Voltage	18-30 V DC
Lamp power	1.45 W
Operational temperature	-40 °C - +70 °C

DIMENSIONS

Height	65 mm
Diameter	50 mm
Width	50 mm
Weight	47 g

ADDITIONAL DATA

IP class	IP66, IP67, IP69, IP6K9K
IK class	8

Supply voltage dc max	30 V DC
Supply voltage dc min	18 V DC
Temperature operational min	-40 °C
Temperature operational max	70 °C
Life span	60000 h