0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

## **AUER PANEL MOUNTED BUZZER**

813500310 Panel mount buzzer, Ø45mm, Black, 110-120 V ac, **ESM** 

- Panel mounted buzzer with loud sound level
- · Adjustable volume
- 3 selectable sound signals
- For mounting in drilled holes 22.5 mm or 30.5 mm



## PRODUCT DESCRIPTION

Panel mounted buzzer with wide voltage range and high enclosure class, IP65. Excellent when you want to call for extra attention in a panel.

## **TECHNICAL DATA**

Diameter	45 mm
Housing Colour	Black
IP class	IP65
Nominal current max	0.042 A
Number of optional modules	0
Number of tones	2
Sound level max	100 dB
Sound level min	85 dB
Supply voltage ac max	140 V AC
Supply voltage ac min	75 V AC
Supply voltage ac/dc max	24 V
Temperature operational max	60 °C
Temperature operational min	-25 °C
Terminal connection	2.5 mm²



Justerbar volym med hjälp av potentiometer, (ej ESK.)



The distance, the following distance table is to be seen as indicators, as also factors to take in the following distance table is to be seen as indicators, as also factors to take in the following the following



Justerbar volym med hjälp av potentiometer, (ej ESK.)

