



ASCO - 2/2 STEAM VALVE 3/8"-3/4"

SCE222D001

Solenoid valve 2/2 NC 3/8" 230/50

- Normally closed
- Media temperature up to +180 °C
- Working pressure 0 to 9 bar steam
- Housing in brass



PRODUCT DESCRIPTION

TECHNICAL DATA

GENERAL DATA

Connection	3/8 BSP
Flow factor / flow coefficient	2,4
IP class	IP65

MATERIAL DATA

Material body	Brass
Material of seals	PTFE
Material seat	Brass

TEMPERATURE DATA

Temperature of media from	-20 °C
Temperature of media to	184 °C

ADDITIONAL DATA

Pressure max	10 bar
Close delay	75 ms
Weight	1,3 kg

Power consumption	16,7 W
Throughput	16 mm
Type of valve	Solenoid valve
Response time off	100 ms
Voltage AC	230 V
Temperature operational min	-20 °C
Temperature operational max	40 °C
Material coil	Epoxy
Differential pressure max	9 bar
Differential pressure min	0 bar
Flow max	40 l/min
Function 1	2/2
Function 2	Normally Closed (SPST)
Material flask	Brass
Material piston ring	PTFE flask filled
Material plunger	Stainless steel
Material short-circuit ring	Copper
Material spring	Stainless steel

