



## ASCO - 2/2 PROPORTIONAL VALVE 1/4"

SCG202A001VS3

Proportional valve 2/2 NC 1/4" 24VDC"

- Normally closed
- Compact version
- Working pressure 0 to 16 bar
- Housing in brass or stainless



### PRODUCT DESCRIPTION

### TECHNICAL DATA

#### GENERAL DATA

Connection	1/4 BSP
Flow factor / flow coefficient	0,05
IP class	IP65

#### MATERIAL DATA

Material body	Brass
Material seat	Brass

#### TEMPERATURE DATA

Temperature of media from	-10 °C
Temperature of media to	90 °C

#### ADDITIONAL DATA

Pressure max	35 bar
Viscosity max	21 cSt
Weight	0,5 kg
Power consumption	8 W

Throughput	1,2 mm
Sensitivity	<2%
Voltage dc	24 V
Temperature operational min	-10 °C
Temperature operational max	75 °C
Material coil	Epoxy
Differential air pressure max	16 bar
Differential pressure min	0 bar
Differential pressure vacuum max	1 bar
Flow max	0,8 l/min
Function 1	2/2
Function 2	Normally Closed (SPST)
Material plunger	Stainless steel
Material glide ring	PTFE
Material seat seal	FPM
Material spring	Stainless steel

