

**ASCO - 238 SERIES PILOT OPERATED**

2/2

SCG238A044  
Solenoid valve 2/2 NC 3/8" 230/50

- Normally closed
- 3/8" up to 2" pipe size
- Air, inert gas & water
- Housing in brass or stainless steel
- Flow rates from 2.1 up to 34 m<sup>3</sup>/h



## PRODUCT DESCRIPTION

**TECHNICAL DATA****GENERAL DATA**

Connection	G3/8
Flow factor / flow coefficient	2,1
IP class	IP65

**MATERIAL DATA**

Material body	Brass
Material of seals	NBR
Material seat	Brass
Material internal parts	Stainless steel

**TEMPERATURE DATA**

Temperature of media from	-20 °C
Temperature of media to	85 °C

**ADDITIONAL DATA**

Pressure max	16 bar
Viscosity max	40 cSt

<b>Weight</b>	0.55 kg
<b>Power consumption</b>	6 W
<b>Throughput</b>	12.5 mm
<b>RSK number</b>	4528043
<b>Voltage AC</b>	230 V
<b>Temperature operational min</b>	-20 °C
<b>Temperature operational max</b>	75 °C
<b>Material coil</b>	Epoxy
<b>Differential air pressure max</b>	10 bar
<b>Differential pressure max</b>	10 bar
<b>Differential pressure min</b>	0 bar
<b>Differential water pressure max</b>	10 bar
<b>Flow max</b>	35 l/min
<b>Function 1</b>	2/2
<b>Function 2</b>	Normally Closed
<b>Material plunger</b>	Stainless steel
<b>Material short-circuit ring</b>	Copper
<b>Material membrane</b>	NBR

