



ASCO - 238 SERIES PILOT OPERATED

2/2

SCG238A048
Solenoid valve 2/2 NC 3/4" 230/50

- Normally closed
- 3/8" up to 2" pipe size
- Air, inert gas & water
- Housing in brass or stainless steel
- Flow rates from 2.1 up to 34 m3/h



PRODUCT DESCRIPTION

TECHNICAL DATA

GENERAL DATA

Connection	G3/4
Flow factor / flow coefficient	10
IP class	IP65

MATERIAL DATA

Material body	Brass
Material of seals	NBR
Material seat	Brass
Material internal parts	Stainless steel

TEMPERATURE DATA

Temperature of media from	-20 °C
Temperature of media to	85 °C

ADDITIONAL DATA

Pressure max	16 bar
Viscosity max	40 cSt

Weight	1.3 kg
Power consumption	6 W
Throughput	25 mm
Voltage AC	230 V
Temperature operational min	-20 °C
Temperature operational max	50 °C
Material coil	Epoxy
Differential air pressure max	10 bar
Differential pressure max	10 bar
Differential pressure min	0 bar
Differential water pressure max	10 bar
Flow max	166 l/min
Function 1	2/2
Function 2	Normally Closed (SPST)
Material plunger	Stainless steel
Material short-circuit ring	Copper
Material membrane	NBR

