OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

ASCO - 215 SERIES DIRECT OPERATED

2/2

SCE215C010
Solenoid valve 2/2 NC 3/8" 230/50



- Normally closed
- Housing in aluminium
- Working pressure 0 bar to 3.5 bar

PRODUCT DESCRIPTION

TECHNICAL DATA

GENERAL DATA

Connection	3/8 BSP
Flow factor / flow coefficient	2,9
IP class	IP65

MATERIAL DATA

Material body	Aluminium
Material of seals	NBR
Material seat	Aluminium

TEMPERATURE DATA

Temperature of media from	-20 °C
Temperature of media to	85 °C

ADDITIONAL DATA

Weight	0.6 kg

Power consumption	10.5 W

Throughput	19 mm
Type of valve	Solenoid valve
Voltage AC	230 V
Temperature operational min	-20 °C
Temperature operational max	75 °C
Material coil	Epoxy
Differential air pressure max	3.5 bar
Differential pressure max	3.5 bar
Differential pressure min	0 bar
Flow max	48.3 l/min
Function 1	2/2
Function 2	Normally Closed
Material plunger	Stainless steel
Material short-circuit ring	Copper
Material glide ring	PTFE
Material spring	Stainless steel

