



## ASCO - 215 SERIES DIRECT OPERATED

2/2

SCE215B060  
Solenoid valve 2/2 NC 1 1/4" 230/50

- Normally closed
- Housing in aluminium
- Working pressure 0 bar to 3.5 bar



### PRODUCT DESCRIPTION

### TECHNICAL DATA

#### GENERAL DATA

Connection	1 1/4 BSP
Flow factor / flow coefficient	27
IP class	IP65

#### MATERIAL DATA

Material body	Aluminium
Material of seals	NBR
Material seat	Aluminium

#### TEMPERATURE DATA

Temperature of media from	-20 °C
Temperature of media to	85 °C

#### ADDITIONAL DATA

Weight	1.8 kg
Power consumption	15.4 W

Throughput	41 mm
Type of valve	Solenoid valve
Voltage AC	230 V
Temperature operational min	-20 °C
Temperature operational max	75 °C
Material coil	Epoxy
Differential air pressure max	1.8 bar
Differential pressure max	1.8 bar
Differential pressure min	0 bar
Flow max	450 l/min
Function 1	2/2
Function 2	Normally Closed (SPST)
Material plunger	Stainless steel
Material short-circuit ring	Copper
Material glide ring	PTFE
Material spring	Stainless steel

