OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

ASCO - 327 SERIES DIRECT OPERATED

3/2

SCG327B001
Solenoid valve 3/2 U 1/4" 230/50



- Universal function
- Large flow
- Working pressure 0 to 10 bar
- Housing in brass or stainless

PRODUCT DESCRIPTION

TECHNICAL DATA

GENERAL DATA

Flow factor / flow coefficient	0,45
IP class	IP65

MATERIAL DATA

Material body	Brass
Material of seals	FPM

TEMPERATURE DATA

Temperature of media from	-20 °C
Temperature of media to	120 °C

ADDITIONAL DATA

Response time	100 ms
Viscosity max	65 cSt
Weight	0.95 kg

Power consumption	10 W

Throughput	5.7 mm
Type of valve	Solenoid valve
Voltage AC	230 V
Temperature operational min	-40 °C
Temperature operational max	55 °C
Material coil	Epoxy
Connection port 1-2	G1/4
Connection port 3	G1/4
Differential air pressure max	10 bar
Differential pressure max	10 bar
Differential pressure min	0 bar
Differential water pressure max	10 bar
Flow max	7.5 l/min
Function 1	3/2
Function 2	Universal
Material plunger	Stainless steel
Material glide ring	PTFE
Material seat seal	FPM
Material spring	Stainless steel





