



## ASCO - 210 SERIES PILOT OPERATED

2/2

SCE210D001  
Solenoid valve 2/2 NC 3/8" 230/50

- Normally closed or normally open
- 3/8" up to 1 1/2" pipe size
- Air, inert gas, water & oil
- Housing in brass or stainless steel
- Flow rates from 2.6 up to 19.3 m<sup>3</sup>/h



### PRODUCT DESCRIPTION

### TECHNICAL DATA

#### GENERAL DATA

Connection	3/8 BSP
Flow factor / flow coefficient	2,6

#### MATERIAL DATA

Material body	Brass
Material of seals	NBR
Material seat	Brass

#### TEMPERATURE DATA

Temperature of media from	-20 °C
Temperature of media to	85 °C

#### ADDITIONAL DATA

Pressure max	20 bar
Close delay	15 ms
Viscosity max	65 cSt
Weight	0.8 kg

<b>Power consumption</b>	6 W
<b>Throughput</b>	16 mm
<b>Type of valve</b>	Solenoid valve
<b>Response time off</b>	60 ms
<b>Voltage AC</b>	230 V
<b>Temperature operational min</b>	-20 °C
<b>Temperature operational max</b>	75 °C
<b>Material coil</b>	Epoxy
<b>Differential air pressure max</b>	14 bar
<b>Differential pressure max</b>	14 bar
<b>Differential pressure min</b>	0.35 bar
<b>Differential oil pressure max</b>	10 bar
<b>Differential water pressure max</b>	10 bar
<b>Flow max</b>	43 l/min
<b>Function 1</b>	2/2
<b>Function 2</b>	Normally Closed
<b>Material plunger</b>	Stainless steel
<b>Material short-circuit ring</b>	Copper
<b>Material spring</b>	Stainless steel
<b>Material membrane</b>	NBR

