



ASCO - 210 SERIES PILOT OPERATED

2/2

SCE210D002
Solenoid valve 2/2 NC 1/2" 230/50

- Normally closed or normally open
- 3/8" up to 1 1/2" pipe size
- Air, inert gas, water & oil
- Housing in brass or stainless steel
- Flow rates from 2.6 up to 19.3 m³/h



PRODUCT DESCRIPTION

TECHNICAL DATA

GENERAL DATA

Connection	1/2 BSP
Flow factor / flow coefficient	3,4

MATERIAL DATA

Material body	Brass
Material of seals	NBR
Material seat	Brass

TEMPERATURE DATA

Temperature of media from	-20 °C
Temperature of media to	85 °C

ADDITIONAL DATA

Pressure max	20 bar
Close delay	15 ms
Viscosity max	65 cSt
Weight	0.8 kg

Power consumption	6 W
Throughput	16 mm
Type of valve	Solenoid valve
Response time off	60 ms
Voltage AC	230 V
Temperature operational min	-20 °C
Temperature operational max	75 °C
Material coil	Epoxy
Differential air pressure max	14 bar
Differential pressure max	14 bar
Differential pressure min	0.35 bar
Differential oil pressure max	10 bar
Differential water pressure max	10 bar
Flow max	57 l/min
Function 1	2/2
Function 2	Normally Closed (SPST)
Material plunger	Stainless steel
Material short-circuit ring	Copper
Material spring	Stainless steel
Material membrane	NBR

