

0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

# ASCO - 2/2 SERVO-CONTROLLED 1/4\"-3/4\"

SCB223A125 Solenoid valve 2/2 NC 1/4" 230/50

- Normally closed
- For high pressure
- Standard working pressure 0.7 bar to 100 bar
- Housing in brass or stainless



### PRODUCT DESCRIPTION

## **TECHNICAL DATA**

### **GENERAL DATA**

Connection	1/4 BSP
Flow factor / flow coefficient	1,3
IP class	IP65

## **MATERIAL DATA**

Material body	Brass
Material of seals	NBR
Material seat	Brass

## **TEMPERATURE DATA**

Temperature of media from	-20 °C
Temperature of media to	90 °C

## **ADDITIONAL DATA**

Pressure max	100 bar
Close delay	15 ms
Viscosity max	65 cSt



Weight	0.7 kg
Power consumption	16.7 W
Throughput	8 mm
Type of valve	Solenoid valve
Response time off	60 ms
Voltage AC	230 V
Temperature operational min	-20 °C
Temperature operational max	50 °C
Material coil	Ероху
Differential air pressure max	100 bar
Differential pressure max	100 bar
Differential pressure min	0.7 bar
Differential oil pressure max	100 bar
Differential water pressure max	100 bar
Flow max	21.7 l/min
Function 1	2/2
Function 2	Normally Closed
Material flask	Stainless steel
Material plunger	Stainless steel
Material short-circuit ring	Copper
Material glide ring	PTFE
Material piston seal	PTFE
Material seat seal	Urethane

