

**ASCO - 2/2 STEAM VALVE 3/8"-3/4"**

SCE222D001

Solenoid valve 2/2 NC 3/8" 230/50

- Normally closed
- Media temperature up to +180 °C
- Working pressure 0 to 9 bar steam
- Housing in brass

**PRODUCT DESCRIPTION****TECHNICAL DATA****GENERAL DATA**

Connection	3/8 BSP
Flow factor / flow coefficient	2,4
IP class	IP65

**MATERIAL DATA**

Material body	Brass
Material of seals	PTFE
Material seat	Brass

**TEMPERATURE DATA**

Temperature of media from	-20 °C
Temperature of media to	184 °C

**ADDITIONAL DATA**

Pressure max	10 bar
Close delay	75 ms
Weight	1.3 kg

<b>Power consumption</b>	16.7 W
<b>Throughput</b>	16 mm
<b>Type of valve</b>	Solenoid valve
<b>Response time off</b>	100 ms
<b>Voltage AC</b>	230 V
<b>Temperature operational min</b>	-20 °C
<b>Temperature operational max</b>	40 °C
<b>Material coil</b>	Epoxy
<b>Differential pressure max</b>	9 bar
<b>Differential pressure min</b>	0 bar
<b>Flow max</b>	40 l/min
<b>Function 1</b>	2/2
<b>Function 2</b>	Normally Closed
<b>Material flask</b>	Brass
<b>Material piston ring</b>	PTFE flask filled
<b>Material plunger</b>	Stainless steel
<b>Material short-circuit ring</b>	Copper
<b>Material spring</b>	Stainless steel

