



ASCO - 2/2 SEAT VALVE AIR CONTROLLED 1/2"-2"

E298A004

- Normally closed, normally open
- Working pressure 0 to 40 bar
- For temperatures up to +250 °C
- For viscosity up to 5,000 cSt



PRODUCT DESCRIPTION

TECHNICAL DATA

GENERAL DATA

Connection	1 1/4 BSP
------------	-----------

MATERIAL DATA

Material body	Stainless steel 316L
Material of seals	Graphite

TEMPERATURE DATA

Temperature of media from	-10 °C
Temperature of media to	250 °C

ADDITIONAL DATA

Viscosity max	5000 cSt
Weight	9.32 kg
Throughput	32 mm
Type of valve	Seat valve
Material packing	Stainless steel
Pilot pressure max	10 bar

Temperature operational min	-25 °C
Temperature operational max	180 °C
Connection air	1/4 BSP
Differential air pressure max	40 bar
Differential pressure max	40 bar
Differential pressure min	0 bar
Differential oil pressure max	40 bar
Differential water pressure max	40 bar
Differential steam pressure max	40 bar
Function 1	2/2
Function 2	Normally Closed (SPST)
Material controls	Nickel plated aluminum
Material piston rod	Stainless steel
Material box stuffing	PTFE flask filled
Material piston seal	Bronze, PTFE

