

OEM Automatic Ltd

Address: Whiteacres, Whetstone Leicester, LE8 6ZG 0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

ASCO - 2/2 SEAT VALVE AIR CONTROLLED 1/2"-2"

E298A009

Pressure op. valve 2/2 NO 1" Stainless.St

- Normally closed, normally open
- Working pressure 0 to 40 bar
- For temperatures up to +250 °C
- For viscosity up to 5,000 cSt



PRODUCT DESCRIPTION

TECHNICAL DATA

GENERAL DATA

Connection

MATERIAL DATA	
Material body	Stainless steel 316L
Material of seals	Graphite
TEMPERATURE DATA	
Temperature of media from	-10 °C
Temperature of media to	250 °C
ADDITIONAL DATA	

G1

ADDITIONAL DATA

Viscosity max	5000 cSt
Weight	4.12 kg
Throughput	25 mm
Type of valve	Seat valve
Material packing	Stainless steel
Pilot pressure max	10 bar

Temperature operational min	-25 °C
Temperature operational max	180 °C
Connection air	1/8 BSP
Differential air pressure max	40 bar
Differential pressure max	40 bar
Differential pressure min	0 bar
Differential oil pressure max	40 bar
Differential water pressure max	40 bar
Differential steam pressure max	40 bar
Function 1	2/2
Function 2	Normally open (SPST)
Material controls	Nickel plated aluminum
Material piston rod	Stainless steel
Material box stuffing	PTFE flask filled
Material piston seal	Bronze, PTFE

