



## ASCO - 2/2 SEAT VALVE AIR CONTROLLED 1/2"-2"

E298A012

Pressure op. valve 2/2 NO 2" Stainless.St

- Normally closed, normally open
- Working pressure 0 to 40 bar
- For temperatures up to +250 °C
- For viscosity up to 5,000 cSt



### PRODUCT DESCRIPTION

### TECHNICAL DATA

#### GENERAL DATA

Connection	G2
------------	----

#### MATERIAL DATA

Material body	Stainless steel 316L
Material of seals	Graphite

#### TEMPERATURE DATA

Temperature of media from	-10 °C
Temperature of media to	250 °C

#### ADDITIONAL DATA

Viscosity max	5000 cSt
Weight	21.68 kg
Throughput	50 mm
Type of valve	Seat valve
Material packing	Stainless steel
Pilot pressure max	10 bar

Temperature operational min	-25 °C
Temperature operational max	180 °C
Connection air	1/4 BSP
Differential air pressure max	40 bar
Differential pressure max	40 bar
Differential pressure min	0 bar
Differential oil pressure max	40 bar
Differential water pressure max	40 bar
Differential steam pressure max	40 bar
Function 1	2/2
Function 2	Normally open (SPST)
Material controls	Nickel plated aluminum
Material piston rod	Stainless steel
Material box stuffing	PTFE flask filled
Material piston seal	Bronze, PTFE

