



## ASCO - 2/2 PROPORTIONAL VALVE M5

SCS202A107VS3

Proportional Valve 2/2 NC. M5, 24VDC

- Normally closed
- Compact version
- Working pressure 0 to 12 bar
- Housing in brass



### PRODUCT DESCRIPTION

### TECHNICAL DATA

#### GENERAL DATA

|            |    |
|------------|----|
| Connection | M5 |
|------------|----|

#### MATERIAL DATA

|               |       |
|---------------|-------|
| Material body | Brass |
|---------------|-------|

#### TEMPERATURE DATA

|                           |      |
|---------------------------|------|
| Temperature of media from | 0 °C |
|---------------------------|------|

|                         |       |
|-------------------------|-------|
| Temperature of media to | 60 °C |
|-------------------------|-------|

|            |        |
|------------|--------|
| Throughput | 1.6 mm |
|------------|--------|

|                               |       |
|-------------------------------|-------|
| Differential air pressure max | 4 bar |
|-------------------------------|-------|

|                           |       |
|---------------------------|-------|
| Differential pressure max | 4 bar |
|---------------------------|-------|

|                           |       |
|---------------------------|-------|
| Differential pressure min | 0 bar |
|---------------------------|-------|

|                                  |       |
|----------------------------------|-------|
| Differential pressure vacuum max | 1 bar |
|----------------------------------|-------|

|          |           |
|----------|-----------|
| Flow max | 1.3 l/min |
|----------|-----------|

|            |     |
|------------|-----|
| Function 1 | 2/2 |
|------------|-----|

|            |                        |
|------------|------------------------|
| Function 2 | Normally Closed (SPST) |
|------------|------------------------|

