

**ASCO - 2/2 STEAM VALVE 3/8"-1 1/2"**

SCE222B094

Solenoid valve 2/2 NC 1/2" 230/50

- Normally closed
- Media temperature up to +150 °C
- Working pressure 0 to 3.5 bar steam
- Housing in brass

**PRODUCT DESCRIPTION****TECHNICAL DATA****GENERAL DATA**

Connection	1/2 BSP
Flow factor / flow coefficient	3,5
IP class	IP65

**MATERIAL DATA**

Material body	Brass
Material of seals	EPDM
Material seat	Brass

**TEMPERATURE DATA**

Temperature of media from	-20 °C
Temperature of media to	150 °C

**ADDITIONAL DATA**

Pressure max	10 bar
Close delay	15 ms
Weight	1.2 kg

<b>Power consumption</b>	10.5 W
<b>Throughput</b>	16 mm
<b>Type of valve</b>	Solenoid valve
<b>Response time off</b>	60 ms
<b>Voltage AC</b>	230 V
<b>Temperature operational min</b>	-20 °C
<b>Temperature operational max</b>	40 °C
<b>Material coil</b>	Epoxy
<b>Differential pressure min</b>	0 bar
<b>Differential steam pressure max</b>	3.5 bar
<b>Flow max</b>	58.3 l/min
<b>Function 1</b>	2/2
<b>Function 2</b>	Normally Closed (SPST)
<b>Material plunger</b>	Stainless steel
<b>Material short-circuit ring</b>	Copper
<b>Material spring</b>	Stainless steel

