



ASCO - 2/2 STEAM VALVE 3/8"-1 1/2"

SCE222B156

Solenoid valve 2/2 NC 1 1/2" 230/50

- Normally closed
- Media temperature up to +150 °C
- Working pressure 0 to 3.5 bar steam
- Housing in brass



PRODUCT DESCRIPTION

TECHNICAL DATA

GENERAL DATA

Connection	1 1/2 BSP
Flow factor / flow coefficient	19,3
IP class	IP65

MATERIAL DATA

Material body	Brass
Material of seals	EPDM
Material seat	Brass

TEMPERATURE DATA

Temperature of media from	-20 °C
Temperature of media to	130 °C

ADDITIONAL DATA

Pressure max	10 bar
Close delay	15 ms
Weight	2.6 kg

Power consumption	15.4 W
Throughput	32 mm
Type of valve	Solenoid valve
Response time off	60 ms
Voltage AC	230 V
Temperature operational min	-20 °C
Temperature operational max	40 °C
Material coil	Epoxy
Differential pressure min	0 bar
Differential water pressure max	9 bar
Differential steam pressure max	2 bar
Flow max	321.6 l/min
Function 1	2/2
Function 2	Normally Closed (SPST)
Material plunger	Stainless steel
Material short-circuit ring	Copper
Material spring	Stainless steel

