



ASCO - 2/2 STEAM VALVE 3/8"-1 1/2"

SCE222B093

Solenoid valve 2/2 NC 3/8" 230/50

- Normally closed
- Media temperature up to +150 °C
- Working pressure 0 to 3.5 bar steam
- Housing in brass



PRODUCT DESCRIPTION

TECHNICAL DATA

GENERAL DATA

Connection	3/8 BSP
Flow factor / flow coefficient	2,6
IP class	IP65

MATERIAL DATA

Material body	Brass
Material of seals	EPDM
Material seat	Brass

TEMPERATURE DATA

Temperature of media from	-20 °C
Temperature of media to	150 °C

ADDITIONAL DATA

Pressure max	10 bar
Close delay	15 ms
Weight	1.2 kg

Power consumption	10.5 W
Throughput	16 mm
Type of valve	Solenoid valve
Response time off	60 ms
Voltage AC	230 V
Temperature operational min	-20 °C
Temperature operational max	40 °C
Material coil	Epoxy
Differential pressure min	0 bar
Differential steam pressure max	3.5 bar
Flow max	43.3 l/min
Function 1	2/2
Function 2	Normally Closed
Material plunger	Stainless steel
Material short-circuit ring	Copper
Material spring	Stainless steel

