

ASCO - 2/2 STEAM VALVE 3/8"-2"

SCE220A019

Solenoid valve 2/2 NC 3/8" 230/50

- Normally closed
- Media temperature up to +185 °C
- Working pressure 0.35 to 10 bar steam
- Housing in brass

**PRODUCT DESCRIPTION****TECHNICAL DATA****GENERAL DATA**

Connection	3/8 BSP
IP class	IP65

MATERIAL DATA

Material body	Brass
Material of seals	EPDM
Material seat	Brass

TEMPERATURE DATA

Temperature of media from	-20 °C
Temperature of media to	184 °C

ADDITIONAL DATA

Pressure max	10 bar
Close delay	40 ms
Power consumption	10.5 W

Throughput	16 mm
Type of valve	Solenoid valve
Response time off	120 ms
Voltage AC	230 V
Temperature operational min	-20 °C
Temperature operational max	40 °C
Material coil	Epoxy
Differential air pressure max	10 bar
Differential pressure max	10 bar
Differential pressure min	0.35 bar
Differential water pressure max	10 bar
Flow max	43 l/min
Function 1	2/2
Function 2	Normally Closed
Material plunger	Stainless steel
Material short-circuit ring	Copper
Material seat seal	PTFE
Material spring	Stainless steel

