



## ASCO - 2/2 STEAM VALVE 3/8"-2"

SCE220A019

Solenoid valve 2/2 NC 3/8" 230/50

- Normally closed
- Media temperature up to +185 °C
- Working pressure 0.35 to 10 bar steam
- Housing in brass



### PRODUCT DESCRIPTION

## TECHNICAL DATA

### GENERAL DATA

Connection	3/8 BSP
IP class	IP65

### MATERIAL DATA

Material body	Brass
Material of seals	EPDM
Material seat	Brass

### TEMPERATURE DATA

Temperature of media from	-20 °C
Temperature of media to	184 °C

### ADDITIONAL DATA

Pressure max	10 bar
Close delay	40 ms
Power consumption	10.5 W

<b>Throughput</b>	16 mm
<b>Type of valve</b>	Solenoid valve
<b>Response time off</b>	120 ms
<b>Voltage AC</b>	230 V
<b>Temperature operational min</b>	-20 °C
<b>Temperature operational max</b>	40 °C
<b>Material coil</b>	Epoxy
<b>Differential air pressure max</b>	10 bar
<b>Differential pressure max</b>	10 bar
<b>Differential pressure min</b>	0.35 bar
<b>Differential water pressure max</b>	10 bar
<b>Flow max</b>	43 l/min
<b>Function 1</b>	2/2
<b>Function 2</b>	Normally Closed
<b>Material plunger</b>	Stainless steel
<b>Material short-circuit ring</b>	Copper
<b>Material seat seal</b>	PTFE
<b>Material spring</b>	Stainless steel

