



ASCO - 2/2 STEAM VALVE 3/8"-2"

SCE220031

Solenoid valve 2/2 NC 2" 230VAC

- Normally closed
- Media temperature up to +185 °C
- Working pressure 0.35 to 10 bar steam
- Housing in brass



PRODUCT DESCRIPTION

TECHNICAL DATA

GENERAL DATA

Connection	G2
IP class	IP65

MATERIAL DATA

Material body	Brass
Material of seals	EPDM
Material seat	Brass

TEMPERATURE DATA

Temperature of media from	-20 °C
Temperature of media to	184 °C

ADDITIONAL DATA

Pressure max	10 bar
Close delay	40 ms
Power consumption	10.5 W

Throughput	44 mm
Type of valve	Solenoid valve
Response time off	120 ms
Voltage AC	230 V
Temperature operational min	-20 °C
Temperature operational max	40 °C
Material coil	Epoxy
Differential air pressure max	10 bar
Differential pressure max	10 bar
Differential pressure min	0.35 bar
Differential water pressure max	10 bar
Flow max	617 l/min
Function 1	2/2
Function 2	Normally Closed (SPST)
Material plunger	Stainless steel
Material short-circuit ring	Copper
Material seat seal	PTFE
Material spring	Stainless steel

